



LIA

LB6059.599-EN

CE IK08 IP66 



NEW




[SYM-4L]

Symmetric, 360°,  
Special effect: 4  
lines - 360x20°

### Variants

<b>Light distribution</b>	[SYM-4L] 360x20°
<b>Nominal LED lumens flux</b>	3267 - 3367 lm
<b>Nominal LED power</b>	35 W (700 mA)
<b>Rated luminaire lumens flux</b>	472 - 485 lm
<b>Rated luminaire power</b>	40 W
<b>Colour temperature</b>	3000 K CRI 80, 4000 K CRI 80
<b>BUG rating</b>	B0-U0-G1, B0-U0-G0
<b>Lifetime L90B50</b>	>55,000
<b>Lifetime L80B50</b>	>55,000

### Options

<b>Control</b>	On/Off
<b>Input voltage</b>	220-240V 50/60Hz, 120-277V 50/60Hz
<b>Insulation class</b>	Class I
<b>Product colours</b>	

### Extras

<b>Finishing options</b>	Marine grade coating
--------------------------	----------------------

### Technical information

<b>Mounting</b>	Surface mountable
<b>Housing</b>	Corrosion resistant, marine grade aluminum housing
<b>Finishing</b>	Corrosion resistant, extruded, marine grade aluminum housing
<b>Fasteners</b>	Stainless steel (grade 304)
<b>Gasket</b>	Silicone
<b>Lens / Reflector</b>	Glass lens with high optical efficiency
<b>Glass / Diffusor</b>	Tempered safety glass
<b>Impact protection</b>	IK08
<b>Ingress protection</b>	IP66
<b>Weight</b>	6.84 kg
<b>LED module</b>	Multi-chip high power LEDs on metal-core PCB
<b>Driver</b>	Internal LED driver
<b>Driver surge protection</b>	4/4 kV
<b>Power factor</b>	> 0.97
<b>Through wiring</b>	Single cable entry
<b>Operating temperature</b>	-40...50°C
<b>Cable</b>	0.5 m of flexible cable

