



# Agis LED 31W 1,50m Warm Continuous

## OUTDOOR > AGIS LED

A tubular luminaire with simple design and a wide light distribution.

The IP67 protection allows even external use.

Applicable to light buildings, residential and industrial areas,

and adaptable to various architectural geometries and creative lighting applications.

### Technical Features

- Opal tube in PMMA, in four different lengths.
- Integrated control gear.
- Aluminium end caps with inox cablegland.
- Through wiring 3x0,75mm<sup>2</sup>, external 1m.
- Pure light without IR/UV radiation.
- 120° light beam distribution.
- Operation life: 50,000 hours with efficiency > 80% of the initial luminous flux (L80B10).
- Connection for operation with 230V/50Hz.



Product Code: 850821

### Version

Dimmer

### Normes



### Description

- PMMA body.
- Aluminium end caps.
- Luminous Efficacy:  
135 Lm/Watt at 3000K 250mA

\* For making continuous row with AGIS it's necessary to use the simple version as the end part.

### Specification

General	
Catalogue Chapter	OUTDOOR
Product Family	AGIS LED
Lamp Category	LED
Fixation	SURFACE or PENDANT
IP	IP 67
Dimensions	1,50m

Drawings	
Dimensional Drawing	<p>15W 660mm, 21W 940mm, 27W 1220mm, 35W 1500mm</p> <p>ø60mm</p>