

BEAM 6 - TWO WAY LED



OUTDOOR > BEAM 5 - BEAM 6 LED IP65

Surface wall mounted luminaire with power LED chip. It is ideal for a wide range of outdoor applications due to its high protection degree IP65. Available with one or two-way light distribution and with different beam angles.

Technical Features

- Aluminium body, painted electrostatically in selected colour.
- Mounting base from die-cast aluminium.
- Tempered protection glass.
- Beam distribution lens.
- Silicone sealant.
- Pure light without IR/UV radiation.
- Operation life: 50,000 hours with efficiency > 80% of the initial luminous flux (L80B10).

Upon request:

Available with highest colour rendering index (CRI)

To ensure the degree of protection (sealing), the use of flexible power supply cable type HO7RN-F is required.

Product Code: BM6_L_TW

LED Color Codes

Warm Neutral

Beam Codes

Spot/Spot Medium/Medium Wide/Wide Spot/Medium


Spot/Wide Medium/Wide

Color Codes

Colours White Titan Black

Chrome Matt Alum

Normes



Description

- Beams: Spot, Medium, Wide.
- 6x1W power consumption driven at 350mA.
- 6x2W power consumption driven at 500mA.
- CRI: min. 80 / SCDM: 3
- Luminous Efficacy:
 3+3x1W: 4000 K: 164+164 Lm/Watt
 3+3x1W: 3000 K: 159+159 Lm/Watt
 3+3x2W: 4000 K: 113+113 Lm/Watt
 3+3x2W: 3000 K: 106+106 Lm/Watt

Specification

General

Catalogue Chapter	OUTDOOR
Product Family	BEAM 5 / BEAM 6 LED IP65
Lamp Category	LED
Fixation	WALL
IP	IP 65

Drawings

BEAM 6 - TWO WAY LED

Dimensional Drawing

